Review Positioning, Make a menu page

Preview - Let's Make a Menu Page

Launch Page / Menu Design

Mark MacCabe

Link Link Link Link Link	Random Cool Info
--------------------------------------	------------------

(
	Footer
	Totel

Review First!

IDs

The ID attribute is used to create a unique id for an element

As good practice an ID should be applied to only one element on a page

It is written as follow:

This paragraph has a unique ID attribut@/p>

Using an ID

In CSS to define an ID you use #

```
#paragraphOne {
```

```
background-color: black;
```

```
color: white;
```

```
text-align: left;
```



Classes

The class attribute is used to create a shared "ID" across multiple elements

As good practice a class should be applied to more than one element on a page

It is written as follow:

This paragraph has a unique class attribut@/p>

Using a class

In CSS to define a class you use .

```
.paragraphClass {
```

background-color: blue;

```
color: black;
```

```
text-align: right;
```



Review - DIV

DIVs are empty containers

A DIV does not add or remove anything from a page

DIVs are a great to help style a page

DIVs will become more important in later lessons

Sizing an element such as a DIV or IMG

height:300px;


width:400px;

Sizing issues:

Add 50px padding to one of your divs.

padding:50px;

Now make the divs the same size without changing the padding.



Why is this happening?

By default, the width and height of an element is calculated like this:

width + padding + border = actual width of an element

height + padding + border = actual height of an element

This means: When you set the width/height of an element, the element often appears bigger than you have set (because the element's border and padding are added to the element's specified width/height).

Source: https://www.w3schools.com/css/css3 box-sizing.asp


How do we solve this?

* {box-sizing: border-box;}

If you set box-sizing: border-box; on an element, padding and border are included in the width and height


Arranging DIVs (or other elements) on a page

Mark MacCabe



Positioning on webpages

When you add elements to your page you are creating a series of **blocks** that can be manipulated around your page. Elements behave different based on how they are defined. An example of this is text vs paragraph.



Using the CSS display property

{display: none; } - removes the element

{display: inline;} - displays similar to a span - inline with other elements This is an Anchor tag.

{display: block;} - displays similar to a , starting a new line and claiming the entire block

{display: flex; } - block-level flex container (see next slide)

More about flex:

div {

display: flex;

flex-direction: row;

}

Other Options: row | row-reverse | column | column-reverse | inherit

Another Cool Trick - overflow

The overflow property specifies whether to clip the content or to add scrollbars when the content of an element is too big to fit in the specified area.

The overflow property has the following values:

- visible Default. The overflow is not clipped. The content renders outside the element's box
- hidden The overflow is clipped, and the rest of the content will be invisible
- scroll The overflow is clipped, and a scrollbar is added to see the rest of the content
- auto Similar to scroll, but it adds scrollbars only when necessary

Source: https://www.w3schools.com/css/css_overflow.asp

Example of overflow: visible

By default, the overflow is visible, meaning that it is not clipped and it renders outside the element's box:

You can use the overflow property when you want to have better control of the layout. The overflow property specifies what happens if content overflows an element's box.

Let's finish our menu page

Launch Page / Menu Design

Mark MacCabe

Link Link Link Link	Main Content Goes Here		Random Cool Info
------------------------------	------------------------	--	------------------

<i>r</i>		
		1
	Footer	
		1